

DSP4030

30W Wall-mounted Speaker



Description

DSP4030 Wall-mounted Speaker has multiple access to meet different installation and use needs. It is ideal for outdoor usage, meeting IP54 weatherproof test requirements. With waterproof, windproof and dust-proof characteristics, it can also work reliably for a long time even in harsh outdoor conditions; The speaker is widely applied to such occasions as schools, hospitals, squares, parks, shopping centers, airports, stations, sports venues, etc.

Features

- Multiple access options for different installation and use needs;
- Can be adjusted up/down to 30 degrees as well as left/right to 90 degrees;
- With mature two-way frequency design;
- Meet IP54 weatherproof test requirements;
- ASA material case, aluminum mesh, sunlight, corrosion and aging resistance; waterproof, windproof and dust-proof structure design;
- With stylish and beautiful appearance, excellent sound quality, reliable performance, simple and quick installation;

Specifications

Model	DSP4030
Freq. Response (-3dB)	90Hz-18kHz
Sensitivity (1m,1w)	90dB±2dB
Max. SPL	103dB±2dB
Directivity Angle	Horizontal - 90°; Vertical - 90°
Rated Power	7.5W/15W/30W
Input Mode	Constant Voltage 70V/100V
Input Transformer	Multi-tap Audio Transformer
Shell Material	Aluminum Mesh + ASA box + Fluorine matrix composite Bracket
Suitable Environment	Outdoor
Specification	IP54
Color	Black/White
Net Weight	3.0kg
Dimensions (H* W* D)	292mm*200mm*166mm (including bracket 242mm)
Quantity	2PCS