

FOR USE BY COMPETENT PERSONS

Anyone using this instrument should be knowledgeable and trained about the risks involved with measuring voltage, especially in an industrial setting, and the importance of taking safety precautions and of testing the instrument before and after using it to ensure that it is in good working condition.

Read First: Safety Information



To prevent possible electric shock:

- Read all safety information before using the Product.
- Do not rely on the Tester to detect live conductors for safety purposes. A device such as this Tester is NOT suitable as a single-pole voltage meter or 2-pole voltage detector to detect hazardous voltage prior to commencing work.
- Hold the Product behind the tactile buttons.
- Do not use the Product around explosive or flammable environments.
- Replace all alkaline batteries with the same brand and type to prevent battery leakage.
- Remove the alkaline batteries if the Product is not used for a long period of time, or if stored in temperatures above 40°C. If not removed, battery leakage may result.
- Repair the Product before use if there is a fault that presents a shock hazard or damage the Product.
- Alkaline batteries contain hazardous chemicals. If exposure to chemicals occurs, contact your local health department.
- If the Tester is used in a manner not intended or not provided by the Tester may be a safety hazard.
- Do not use if VoltBeat is not flashing.
- Test on a known live source with the Tester both before and after use to ensure the Tester is working.
- When using the Tester, if tip does not make contact with the Tester indicates active voltage is present. If the Tester indicates sufficient strength emanating from the Tester may not provide indication of voltage if the Tester is unable to detect voltage. This may be influenced by several factors:
 - Shielded wire/cables
 - Thickness and type of insulation
 - Distance from the voltage source
 - Fully-isolated users that prevent contact with the Tester
 - Receptacles in recessed sockets
 - Condition of the Tester and Batteries

2AC

Operating/Storage Temperature: -10 °C to 50 °C






Operating Relative Humidity:

0 % to 95 % 0 °C to 30 °C

0 % to 75 % 30 °C to 40 °C

0 % to 45 % 40 °C to 50 °C

Altitude: 2000 m

	Consult user documentation
	WARNING. HAZARDOUS VOLTAGE
	WARNING. RISK OF DAMAGE
	Double Insulated
	This product complies with the WEEE Directive. The affixed label indicates that this is an electrical/electronic product. Category: With reference to the WEEE Directive