

TECHNICAL DATA

Fluke 324 True-RMS Clamp Meter with Temperature & Capacitance





Key features

"It does everything a HVAC or Maintenance Tech would need. Out of 12 guys I work with 9 of them had the 324" - Thomas

- Rugged, reliable basic True-RMS clamp meter
- Measure AC current up to 400 A, AC/DC voltage to 600V
- Measure resistance up to $4k\Omega$, continuity detection $\leq 30\Omega$
- Additions from 323 Clamp: Temperature, Capacitance, Backlight

Product overview: Fluke 324 True-RMS Clamp Meter with Temperature & Capacitance

The Fluke 324 True-RMS Clamp Meter is a reliable, solid troubleshooting tool for commercial and residential electricians, featuring True-RMS measurements, a slim design for easy transport and use, and a large display for efficient troubleshooting. With the addition of Temperature and Capacitance, it has everything an HVAC technician could need.



Troubleshoot problems safely and accurately

- CAT III 600 V, CAT IV 300 V safety rating
- Provides True RMS AC voltage and current for accurate measurements on non-linear signals
- Measures AC current up to 400 A
- Measures AC/DC voltage to 600V
- Measures resistance to $4k\Omega$ with continuity detection $\leq 30\Omega$
- Measures temperature from -10C to 400C
- Measures capacitance to 1000µF
- Backlight and hold function captures a reading on the display
- Comes with a two-year warranty and soft carrying case

Fluke 320 Series Clamp Meters for electrical troubleshooting







Fluke 323 True-RMS Clamp Meter

Fluke 324 True-RMS Clamp Meter

Fluke 325 True-RMS Clamp Meter

| AC Current | 400A | 40A / 400A | 40A / 400A |
|---------------|------------|----------------|-------------------|
| DC Current | | | 40A / 400A |
| AC/DC Voltage | 600V | 600V | 600V |
| Resistance | 400Ω / 4kΩ | 400Ω / 4kΩ | 400Ω / 4kΩ / 40kΩ |
| Continuity | ≤ 70Ω | ≤ 30Ω | ≤ 30Ω |
| Capacitance | | 100μF / 1000μF | 100μF / 1000μF |
| Temperature | | -10C to 400C | -10C to 400C |
| Backlight | | Yes | Yes |
| Frequency | | | 5Hz to 500Hz |
| Min/Max | | | Yes |

Contents:

- Fluke 324 True-RMS Clamp Meter
- TL75 Test Leads
- Type K Thermocouple
- Two AAA Batteries (Installed)
- Soft Case

Specifications: Fluke 324 True-RMS Clamp Meter with Temperature



& Capacitance

| Specifications | | | |
|---------------------|-------------------|--|--|
| | Range | 40.00 A / 400.0 A | |
| AC current | Accuracy | 1.5% ± 5 digits (45 Hz to 400 Hz) Note: Add 2% for position sensitivity | |
| DC current | Range | - | |
| DC Current | Accuracy | - | |
| AC voltage | Range | 600.0 V | |
| AC voltage | Accuracy | 1.5% ± 5 digits | |
| DC voltage | Range | 600.0 V | |
| DC voltage | Accuracy | 1.0% ± 5 digits | |
| Decistance | Range | 400.0 Ω/ 4000 Ω | |
| Resistance | Accuracy | 1.0% ± 5 digits | |
| Continuity | | ≤ 30 Ω | |
| Capacitance | | 0 to 100.0 μF / 100μF to 1000 μF | |
| Frequency | | - | |
| AC response | | True-RMS | |
| Backlight | | Yes | |
| Data hold | | Yes | |
| Contact temperature | | -10.0°C to 400.0°C (14.0°F to 752.0°F) | |
| Min/Max | | - | |
| | H x W x D (mm) | 207 x 75 x 34 | |
| Size | Max wire diameter | 30 mm (600 MCM) | |
| | Weight | 208 g | |
| Category rating | | CAT III 600 V CAT IV 300 V | |
| Warranty | | Two-year | |



Ordering information



Fluke 324 Fluke 324 True-RMS Clamp Meter

Includes:

- Fluke 324 True-RMS Clamp Meter
- TL75 Test Leads
- Type K Thermocouple
- Two AAA Batteries (Installed)
- Soft Case

| Optional accessories | Description | |
|--|---|--|
| Fluke C11XT Protective EVA Hard Tool Case | Durable EVA foam case with pockets to safely carry most smaller multimeters and accessories | |
| Fluke L210 Probe Light Kit | L210 probe light + probe extenders. Includes L200 probe light and TP280 test probe extenders | |
| Fluke TL175 TwistGuard™ Test Leads | Simply twist to change the exposed probe tip length. | |
| Fluke TL223 SureGrip™ Electrical Test Lead Set | Includes 3 test lead accessories in an all-in-one set. Ideal starter kit for electrical applications. | |

