

# Fast assembly concealed hinge

- ▶ Sensys 110° hinge
- ▶ Opening angle 110°, drilling pattern TH 52 x 5.5 mm



- ▶ Quality classification under EN 15570, Level 3
- ▶ For door thickness 15 - 24 mm
- ▶ Cup depth 12.8 mm
- ▶ Integrated overlay adjustment +2 mm / -2 mm
- ▶ Integrated depth adjustment +3 mm / -2 mm
- ▶ Height adjustment at mounting plate
- ▶ Steel in obsidian black

Drilling pattern	full overlay (Base B 12.5 mm)	half overlay (Base B 3 mm)	inset (Base B -4 mm)

## With integrated Silent System, with self closing feature (Sensys 8645i)

Cup assembly	Mounting hole ø x T mm	full overlay		half overlay		inset	
		50 ea.	200 ea.	50 ea.	200 ea.	50 ea.	200 ea.
For screwing on	-	9 091 738	9 117 734	9 091 739	9 117 736	9 091 740	9 117 737
with expanding sockets	ø 10 x 11	9 091 771	9 117 735	9 091 772		9 091 773	

## Without Silent System, without self closing feature, for handleless applications (Sensys 8675)

Cup assembly	Mounting hole ø x T mm	full overlay	half overlay	inset
		50 ea.	50 ea.	50 ea.
For screwing on	-	9 091 741	9 091 742	9 091 743
with expanding sockets	ø 10 x 11	9 091 774	9 091 775	9 091 776